



CURE HARD

CLEAR DUSTPROOFER AND HARDENER
FOR USE ON INTERIOR OR EXTERIOR CONCRETE SURFACES

CONCRETE 3: CURING COMPOUNDS & LIQUID HARDENERS

PRODUCT DESCRIPTION

Cure Hard is a clear dustproofing and hardener for use on interior or exterior concrete surfaces. Cure Hard contains a unique and exclusive agent that penetrates the pores and capillaries of new or old concrete surfaces to chemically harden and dustproof. The penetrating action of Cure Hard changes free lime in the concrete to calcium silicate.

GENERAL USES

Cure Hard is an excellent treatment for floors to receive asphalt, vinyl or rubber tile and adhesives for carpet. Cure Hard does not leave a residue that must be removed before floor coverings or adhesives can be applied to concrete.

Cure Hard is also the best product for base slabs to receive terrazzo or separate cement toppings.

FEATURES

- One coat application
- Safe to use
- Sprayable—does not clog equipment
- Resilient tiles, carpets, other floor treatments may be applied directly on Cure Hard-treated surfaces
- VOC compliant
- No deleterious effort upon the natural boarding characteristic of secondary toppings and coatings. Consult all manufacturers written instructions

STANDARDS

USDA accepted for use in federally inspected meat and poultry plants.

INSTRUCTIONS FOR USE

Apply Cure Hard when concrete is dry to the touch, or when forms have been removed. Insure that form coatings other than oils have been used. Apply by spray or roller. **DO NOT ALLOW CURE HARD TO PUDDLE.** Brush out puddles as soon as possible.

PRODUCT PROPERTIES

| | |
|-------------------|---|
| APPEARANCE | CLEAR (red fugitive dye available upon request) |
| POUR POINT | 40°F |

Approximate coverage per square feet per gallon

Curing, Hardening and Dustproofing:

| | |
|-----------------------|------------------------------------|
| Hard Troweled Finish | 300 to 500 ft ² /gallon |
| Broom or Float Finish | 200 to 400 ft ² /gallon |
| Rough Finish | 200 to 300 ft ² /gallon |
| Aged Surface | 200 to 300 ft ² /gallon |
| Vertical Surface | 200 to 300 ft ² /gallon |

PACKAGING

- 275 gallon (1040.9 L) totes
- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

LIMITATIONS/WARNING

- Refer to Material Safety Data Sheet before use.
- Designed for use on concrete and masonry only.
- Do not spray on glass, brick, aluminum, etc.
- If accidentally sprayed on other surfaces, wash with clean water before drying.
- Not recommended for use on colored floor surfaces.
- Do not use over colored concrete.
- Do not allow to freeze.
- Do not over apply.

VOC content: 0.0 g/L. Complies with USA and Federal AIM VOC standards.

TECHNICAL SERVICES

Universal Building Products Inc. - Chemical Division Technical Service Department provides complete product and technical support.



universal
Building Products Inc.-Chemical Division

840 SOUTH 25TH AVENUE • BELLWOOD, ILLINOIS 60104 • 800 728 1958

LIMITED WARRANTY NOTICE — Universal Building Products Inc. Chemical Division warrants that at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OR TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Twelve (12) months after Universal Building Products Inc. Chemical Division has shipped the materials, all our Warranty and other duties with respect to the quality of materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any duties may thereafter commence. Universal Building Products Inc. Chemical Division shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured for Universal Building Products Inc. Chemical Division. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salespeople, distributors or representative or by any sales information or drawings.



universal
Building Products Inc. - **Chemical Division**