

MATERIAL SAFETY DATA SHEET

Information Phone # 1-800 728 1958
Latest Revision Date: 01.01.2007
EMERGENCY PHONE #: 1-800 535-5053

Universal Building Products Inc.
840 South 25th Avenue
Bellwood, IL 60104

SECTION I PRODUCT IDENTIFICATION

Trade Name	<i>Maximum</i>		
Chemical Family	Modified Petroleum Oils		
NFPA Ratings (Hazard ID)	Health 1	Fire 1	Reactivity 0
HMS Ratings (Hazard ID)	Health 1	Fire 1	Reactivity 0

Warning! Keep containers (with material or empty) away from sparks, excessive heat, flames, welding. Irritant to skin, eyes. May be fatal if ingested or overexposed. Harmful to lungs, central nervous system, mucous membrane, possibly blood, kidney, liver and reproductive system. Spill may create slipping hazard.

SECTION II INGREDIENTS, LIMITS AND TOXICOLOGICAL INFORMATIONS

INGREDIENT	Refined Petroleum Oil	Petroleum Oil	Mineral Oil	
CAS#	64742-58-1	NA	64742-53-6	
ACGIH TLV/TWA	NA	NA	NA	
ACGIH TLV/STEL	NA	NA	NA	
OSHA PEL/TWA	NA	NA	NA	
OSHA PEL/STEL	NA	NA	NA	
LD50, Oral	NA	NA	NA	
LD 50, Dermal	NA	NA	NA	
LD 50, Inhalation	NA	NA	NA	
PCT BY WT:	0-60	0-60	0-40	

SECTION III PHYSICAL DATA

Physical State	LIQUID	Specific Gravity	.9
Appearance	Clear / Yellow	VOC, Calculated	< 250 g/L
Odor	Low Odor	pH	N/A
Boiling Range	N/A	Freezing Point	N/A
Vapor Pressure	< 0.5 Isoteniscope	Water Solubility	INSOLUBLE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Lowest Closed Cup Flashpoint	Above 200 °F
OSHA Flammability Classification	NA
Lower Flammable Limit in Air	NA
Flash Points	Above 200 °F
Mechanical Impact Explosion	NA
Static Electricity Explosion	NA
EXTINGUISHING MEDIA	Dry chemical or CO2 is preferred

UNUSUAL FIRE AND EXPLOSION HAZARDS:

KEEP CONTAINER TIGHTLY CLOSED AND ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

SPECIAL FIRE FIGHTING PROCEDURES:

FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

SECTION V HEALTH HAZARD DATA

EFFECTS OF EXCESSIVE OVEREXPOSURE-PRIMARY ROUTES OF ENTRY ARE:

PRIMARY ROUTE(S) OF ENTRY:
 INHALATION SKIN INGESTION

SKIN CONTACT:
IRRITATION. CAN CAUSE DEFATTING OF SKIN, WHICH MAY LEAD TO DERMATITIS.

INHALATION:
IRRITATION TO NOSE AND THROAT. EXTENDED OR REPEATED EXPOSURE TO CONTRATIONS ABOVE THE RECOMMENDED EXPOSURE LIMITS MAY CAUSE BRAIN OR NERVOUS SYSTEM DEPRESSION, WITH SYMPTONS SUCH AS DIZZINESS, HEADACHE OR NAUSEA AND IF CONTINUED INDEFINITELY, LOSS OF CONSCIOUSNESS, LIVER AND KIDNEY DAMAGE.

INGESTION:
MAY CAUSE MOUTH, THROAT, ESOPHAGUS AND STOMACH IRRITATION, NAUSEA VOMITING AND DIARRHEA.

MEDICAL CONDITIONS THAT MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT:
PREEXISTING EYE, SKIN, LIVER, KIDNEY AND RESPIRATORY DISORDERS.

EMERGENCY AND FIRST AID PROCEDURES:
IN CASE IF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION; FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPORS OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.

OTHER HEALTH HAZARDS:
LABORATORY ANIMALS EXPOSED TO HIGH DOSES OF XYLENE SHOWED EVIDENCE OF EFFECTS IN THE LIVER, KIDNEYS, LUNGS, CENTRAL NERVOUS SYSTEM, GI TRACT, AND BLOOD FORMING ELEMENTS.

SECTION VI REACTIVITY DATA

STABILITY:
STABLE HAZARDOUS POLYMERIZATION: NONE UNDER NORMAL CONDITIONS.

CONDITIONS TO AVOID:
ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID):
STRONG ACIDS AND STRONG OXIDIZING AGENTS. IF THIS PRODUCT IS NOT WATER REDUCIBLE, AVOID WATER.

HAZARDOUS DECOMPOSITION PRODUCTS:
THERMAL DECOMPOSITION OR COMBUSTION CAN PRODUCE FUMES CONTAINING ORGANIC ACIDS, CARBON DIOXIDE AND CARBON N MONOXIDE.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

WASTE DISPOSAL METHOD:
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE IN APPROVED FACILITY

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:
DON'T BREATHE VAPORS. WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING USE OF THIS PRODUCT UNTIL VAPORS ARE EXHAUSTED, UNLESS AIR MONITORING DEMONSTRATES VAPOR LEVELS ARE BELOW APPLICABLE LIMITS FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE. OBSERVE OSHA STANDARD 29CFR 1910.134.

VENTILATION:
PROVIDE GENERAL CLEAN AIR DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE AIR CONTAMINANT CONCENTRATION BELOW THELOWER EXPLOSION LIMIT AND BELOW CURRENT APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARD 1910.94.

PROTECTIVE GLOVES:
USE SOLVENT IMPERMEABLE GLOVES TO AVOID CONTACT WITH PRODUCT.

EYE PROTECTION:
DO NOT GET IN EYES. USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES, FACE SHIELDS.

OTHER PROTECTIVE EQUIPMENT:
DO NOT GET ON SKIN. USE IMPERMEABLE PROTECTIVE CLOTHING.PREVENT SKIN CONTACT WITH CONTAMINATED CLOTHING. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED CLOTHING. WASH BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED SHOES. EYE BATH AND SAFETY SHOWER SHOULD BE AVAILABLE.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:
 DO NOT PRESURIZE, CUT, WELD, GRIND.DO NOT STORE ABOVE 120° F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM HEAT, SPARKS AND FLAME. KEEP CONTAINERS CLOSED WHEN HOT IN USE AND UPRIGHT TO PREVENT LEAKAGE.

OTHER PRECAUTIONS:
 DO NOT TAKE INTERNALLY. WASH HANDS AFTER USING AND BEFORE SMOKING OR EATING. EMPTIED CONTAINERS MAY RETAIN HAZARDOUS RESIDUE AND EXPLOSIVE VAPORS. KEEP AWAY FORM HEAT, SPARKS, FLAMES AND STATIC ELECTRICITY. DON'T CUT OR WELD ON OR NEAR EMPTIED CONTAINERS. FOLLOW ALL HAZARD PRECAUTIONS GIVEN IN THIS SHEET UNTILL CONTAINER IS THOROUGHLY CLEANED OR DESTROYED.

SECTION X SARA TITLE III INFORMATION

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: N/A

NAME					
CAS#					
PC. WEIGHT					

SECTION XI D.O.T. REGULATIONS (TRANSPORTATION)

Hazard class ID number Packing Group Proper shipping name Label US Domestic Ground Shipments US Domestic Ground Shipments Non Bulk (in containers 119 gal or less)	NA NA III <i>Not Regulated by DOT</i> NA <i>Not Regulated by DOT</i> <i>Not Regulated by DOT</i>
Cross Border transport (ADR/RID) ADR/RID class Danger code (Kemler) UN number Packing group Description	<i>Not Regulated by DOT</i>
Marine transport (IMDG) IMDG class UN number Label Packing group EMS Number Marine pollutant Proper shipping name	N/A
Air transport (ICAO-TI and IATA-DGR) ICAO/IATA class UN number Label Packing group Proper shipping name	N/A

DISCLAIMER AND LIMITATION OF LIABILITY

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the Universal Building Products Inc. knowledge; however, The Universal Building Products Inc. makes no warranty whatsoever, expressed or implied of MERCHANTABILITY or FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained form the use thereof. The Universal Building Products Inc. assumes no responsibility for injury to recipient or to third persons or for any property and recipient assumes all such risk.